







Classic Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Swatch Image		State	Length	Width	Height	Units per sqm	Pack Size	Solar Absorption	Lrv	Basix
Classic	Matte Grey			NSW	440	335	35	9.26	300	0.91	8.9	Dark
Classic	Grey Duo			NSW	440	335	35	9.26	300	0.89	10.9	Dark
Classic	Chestnut			NSW	440	335	35	9.26	300	0.88	10.9	Dark
Classic	Alabaster			NSW	440	335	35	9.26	300	0.28	73.9	Light
Classic	Cool Smoke			NSW	440	335	35	9.26	300	0.93	6.5	Dark
Classic	Linen			NSW	440	335	35	9.26	300	0.55	40.5	Medium
Classic	Aspen			NSW	440	335	35	9.26		0.43	61.5	Light
Classic	Matte Black			NSW	440	335	35	9.26	300	0.95	4.9	Dark
Classic	Silver Gum			NSW	440	335	35	9.26	300	0.73	26.4	Dark
Classic	Vanilla			NSW	440	335	35	9.26		0.43	63.3	Light
Classic	Late Mist			NSW	440	335	35	9.26	300	0.82	16.5	Dark
Classic	Storm Grey			NSW	440	335	35	9.26	300	0.86	14.5	Dark
Classic	Deep Shadow			NSW	440	335	35	9.26	300	0.95	4.7	Dark

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.