

Curvado Glazed Range Technical Data Sheet

BRICKWORKS

Product Range	Name	Swatch Image	State	Length	Width	Height	Units per sqm	Pack Size	Solar Absorption	Lrv	Basix
Curvado Glazed	Trans Roja		NSW	470	286	75	11.4	180	0.62		
Curvado Glazed	Carmine		NSW	470	286	75	11.4	180	0.75	6.8	Dark
Curvado Glazed	Black		NSW	470	286	75	11.4	180	0.9		
Curvado Glazed	White		NSW	470	286	75	11.4	180	0.26	78.5	
Curvado Glazed	Cobalt Azul		NSW	470	286	75	11.4	180	0.84		
Curvado Glazed	Olive Green		NSW	470	286	75	11.4	180	0.83		
Curvado Glazed	Cognac		NSW	470	286	75	11.4	180	0.75		
Curvado Glazed	Honey		NSW	470	286	75	11.4	180	0.67		
Curvado Glazed	Azul		NSW	470	286	75	11.4	180	0.76	10	Dark
Curvado Glazed	Bottle Green		NSW	470	286	75	11.4	180	0.87		Dark
Curvado Glazed	Trans Hispania		NSW	470	286	75	11.4	180	0.61	19	Dark

This Data represents average results from commercial production lots.

If specific test results are required, sample should be taken from current production lots.

AUSTRALIAN STANDARD TEST METHODS AS/NZS 4456 ARE USED AS APPLICABLE.

Please note: FRL applies up to 3m high - restrained on top and bottom.